

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) ~~In a~~ A graphics pipeline ~~including:~~ including:
a recirculating texture unit including a texture coordinate processor, a texture mapper and a texture data feedback path that recirculates selected texture-mapped data from the texture mapper back to the texture coordinate processor; and
a hardware shader that blends selected inputs to provide a calculated color or opacity output that is fed back for use as an input to the hardware shader for a subsequent blending operation, wherein said hardware shader includes a blending operation stage that provides both color blend and alpha blend operations,
wherein said texture coordinate processor interleaves the processing of direct and indirect texture coordinates..

2. (Original) The pipeline of claim 1 wherein an output of the shader can be recirculated to provide n blending stages.

3. (Original) The pipeline of claim 1 wherein recirculation of said shader output allows shade tree type combining operations.

Claim 4 has been canceled without prejudice or disclaimer.

4. (Original) The pipeline of claim 1 wherein the pipeline includes a recirculating texture unit coupled to the shader, and wherein said shader blends a texture output previously provided by the recirculating texture unit while the recirculating texture unit

performs a further texture mapping operation to provide a further texture output for blending by the shader.

~~5.~~
~~6.~~ (Original) The pipeline of claim 1 wherein the shader includes a programmable clamper.

~~6.~~
~~7.~~ (Original) The pipeline of claim 1 wherein the shader includes a programmable scaler.

~~7.~~
~~8.~~ (Original) The pipeline of claim 1 wherein the shader includes a comparator.

~~8.~~
~~9.~~ (Original) The pipeline of claim 1 wherein the shader includes a programmable color swap.

~~9.~~
~~10.~~ (Original) The pipeline of claim 1 wherein an output of the shader is made available as an input for a plurality of subsequent blending operations.

~~10.~~
~~11.~~ (Original) The pipeline of claim 1 wherein the shader includes separate blending circuits for performing both color blend and alpha blend operations during a same blending operation stage.

~~11.~~
~~12.~~ (Original) The pipeline of claim 1 wherein the shader includes a feedback mechanism for providing an output to an input of said shader.

~~12.~~
~~13.~~ (Original) The pipeline of claim ~~12~~ wherein said feedback mechanism includes one or more storage buffers for retaining an output from a blending operation and at least one of said buffers has an output connected to an input of said shader.

~~13.~~
~~14.~~ (Currently amended) In a graphics system, a multi-texturing method comprising:

(a) passing texture mapping data through a component combining arrangement to provide combined textured component outputs;

(b) reconfiguring the component combining arrangement; and

(c) passing said combined textured component outputs through the reconfigured but same component combining arrangement providing both color blend and alpha blend operations to generate combined multi-textured component outputs,

wherein said texture coordinate processor interleaves the processing of direct and indirect texture coordinates..

¹⁴15. (Previously presented) The method of claim ¹³14 wherein said steps (b) and (c) are repeated plural times.

¹⁵16. (Previously presented) The method of claim ¹³14 wherein the component combining arrangement includes a texture color combiner and an alpha combiner.

Claim 17 has been canceled without prejudice or disclaimer.

¹⁶18. (Currently amended) A method for providing multi-textured polygons comprising:

(a) processing texture coordinates;

(a_b) generating first texture mapping data;

(a_c) passing the first texture mapping data through combiner hardware providing both color blend and alpha blend operations to provide a first output corresponding to the first texture mapping data;

(a_d) generating second texture mapping data; and

(de) passing the second texture mapping data and the first output through the combiner hardware to provide a second output corresponding to the first and second texture mapping data,

wherein said generating step (a) interleaves the processing of direct and indirect texture coordinates..

17.
19. (Previously presented) The method of claim 18 wherein step (b) is performed during a blending stage, and step (de) is performed during a further blending stage that is later than the first-mentioned blending stage.

18.
20. (Original) The method of claim 18 wherein the combiner hardware provides more than ten successive stages of texture mapping data blending.

19.
21. (Currently amended) In a graphics rendering pipeline including at least one texture mapping coordinate address unit and a texture environment unit including combiner circuits, an improvement comprising iteratively reusing the combiner circuits to provide multiple stages that apply multiple textures to a surface displayed within an image, wherein said multiple stages each provide both color blend and alpha blend operations, wherein said texture coordinate address unit interleaves the processing of direct and indirect texture coordinates.

20.
22. (Original) The method of claim 19 wherein the iteratively reusing step includes using the combiner circuits to combine first texel colors during a first blending cycle/stage, and using the same combiner circuits to combine second texel colors using a

second blending cycle/stage different from the first cycle/stage, the first and second cycles/stages both falling within a period for generating a single image frame.

~~21.~~ ¹⁹
~~23.~~ (Original) The method of claim ~~21~~ where the first and second cycles/stages are consecutive.

~~22.~~ ¹⁹
~~24.~~ (Previously presented) The method of claim ~~21~~ wherein the combiner circuits include independent color combiner circuits and alpha combiner circuits.

~~23.~~ ¹⁹
~~25.~~ (Previously presented) In a graphics rendering pipeline including at least one texture mapping unit and a texture environment unit including combiner circuits, an improvement comprising iteratively reusing the combiner circuits to provide multiple stages that apply multiple textures to a surface displayed within an image, wherein the combiner circuits compute

$$(D + (-1)^{\text{sub}} * ((1-c) * A + C * B) + \text{bias}) \ll \text{shift}$$

where A, B, C and D are selected from four current-color registers, rasterized color, texture, alpha components, 0 and 1.

~~24.~~ ¹⁹
~~26.~~ (Currently amended) In a graphics system including a processing pipeline that renders and displays images at least in part in response to polygon vertex data and texture data stored in an associated memory, a multitexture processing subsystem for selectively mapping texture data corresponding to one or more different textures and/or texture characteristics to surfaces of said rendered and displayed images, said multitexture processing subsystem comprising:

a recirculating texture unit including a texture coordinate processor, a texture mapper and a texture data feedback path that recirculates selected texture-mapped data from the texture mapper back to the texture coordinate processor; and

a color/alpha-component blending unit configured within the pipeline to combine texture, rasterized color and alpha component data to produce a computed color and a computed alpha and having a feedback mechanism that enables reintroduction of the computed color and computed alpha into the pipeline, wherein a processing of multiple textures is achieved by an iterative use/reuse of the blending unit,

wherein said texture coordinate processor interleaves the processing of direct and indirect texture coordinates.

²⁵
21. (Original) A multitexture processing subsystem as in claim ²⁴20 wherein the blending unit comprises at least one multiplier and one adder and is configured to accept up to four input arguments for performing blending operations.

²⁶
28. (Currently amended) In a graphics system including a processing pipeline that renders and displays images at least in part in response to polygon vertex data and texture data stored in an associated memory, a multitexture processing subsystem for selectively mapping texture data corresponding to one or more different textures and/or texture characteristics to surfaces of said rendered and displayed images, said multitexture processing subsystem comprising:

a recirculating texture unit including a texture coordinate processor, a texture mapper and a texture data feedback path that recirculates selected texture-mapped data from the texture mapper back to the texture coordinate processor; and

a texture environment unit configured within the pipeline to process input texture, color and alpha data during a predetermined processing stage to accomplish a blending and/or mixing of textures and/or colors and alpha data, said texture environment unit including a color/alpha data blending unit having a feedback mechanism operable during selected temporal processing stages wherein an output of a current processing stage is made available as an input to a subsequent processing stage, wherein said texture environment unit provides both color blend and alpha blend operations in a same blending operation stage,

wherein said texture coordinate processor interleaves the processing of direct and indirect texture coordinates.

²⁷
~~29~~. (Original) A multitexture processing subsystem as in claim ²⁶~~28~~ wherein the blending unit is connected to at least one storage register for making an output of a current processing stage available as an input to a subsequent temporal processing stage.

²⁸
~~30~~. (Previously presented) A multitexture processing subsystem as in claim ²⁶~~28~~ wherein the texture environment unit accommodates up to sixteen successive temporal processing stages.

²⁹
~~31~~. (Original) A multitexture processing subsystem as in claim ²⁶~~28~~ wherein the feedback mechanism comprises a plurality of storage registers.

^{30.}
~~32.~~ (Original) A multitexture processing subsystem as in claim ²⁶~~28~~ wherein the blending unit comprises at least one multiplier and one adder and is configured to accept up to four input arguments for performing blending operations.

^{31.}
^{33.} (Currently amended) In a graphics system including a processing pipeline that renders and displays images at least in part in response to polygon vertex data and texture data stored in an associated memory, a multitexture processing subsystem for selectively mapping texture data corresponding to one or more different textures and/or texture characteristics to surfaces of said rendered and displayed images, said multitexture processing subsystem comprising:

a recirculating texture unit including a texture coordinate processor, a texture mapper and a texture data feedback path that recirculates selected texture-mapped data from the texture mapper back to the texture coordinate processor; and

a texture environment unit configured within the pipeline to process input texture and rasterized color data to provide independent mathematical blending operations on input texture and rasterized color data during a predetermined temporal processing cycle/stage, said texture environment unit including a feedback mechanism operated during selected temporal processing cycles/stages wherein an output of a current temporal processing cycle/stage is made available as an input to a subsequent temporal processing cycle/stage, wherein said cycle/stage provides both color blend and alpha blend operations.

wherein said texture coordinate processor interleaves the processing of direct and indirect texture coordinates.

^{32.}
~~34.~~ (Original) A multitexture processing subsystem as in claim ~~33~~³¹ wherein the input texture and rasterized color data comprises RGB and Alpha data.

^{33.}
~~35.~~ (Original) A multitexture processing subsystem as in claim ~~33~~³¹ wherein an output of a texture environment unit temporal processing cycle/stage is available as an input to a subsequent texture environment temporal processing stage.

^{34.}
~~36.~~ (Original) A multitexture processing subsystem as in claim ~~33~~³¹ wherein the texture environment unit may accommodate up to sixteen successive temporal processing stages.

^{35.}
~~37.~~ (Original) A multitexture processing subsystem as in claim ~~33~~³¹ wherein the texture environment unit further comprises a blending unit having at least one multiplier and one adder.

^{36.}
~~38.~~ (Original) A multitexture processing subsystem as in claim ~~33~~³¹ wherein the blending unit is configured to accept up to four input arguments for performing blending operations.

^{37.}
~~39.~~ (Currently amended) In a graphics system including a processing pipeline that renders and displays images at least in part in response to polygon vertex data and texture data stored in an associated memory, a texture processing subsystem for selectively mapping texture data corresponding to one or more different textures and/or texture characteristics to surfaces of said rendered and displayed images, and a texture

environment unit for processing input texture and rasterized color data to provide independent mathematical blending operations on said input texture and rasterized color data, a method for processing multiple textures comprising the steps of:

(a) processing texture coordinates;

~~(a)~~(b) performing blending operations on a first set of texture and rasterized color data during a first texture environment unit temporal processing cycle/stage; and

~~(b)~~(c) providing an output of said first temporal processing cycle/stage as an input to a subsequent texture environment unit temporal processing cycle/stage,

wherein said at least one of said first and subsequent cycles/stages provides both color blend and alpha blend operations, and

wherein said texture coordinate processing step (a) interleaves the processing of direct and indirect texture coordinates.

^{38.}
~~40.~~ (Original) A method for processing multiple textures as in claim ~~39~~³⁷ wherein an output from up to sixteen successive texture environment temporal processing stages may be provided as an input to a subsequent texture environment unit temporal processing cycle/stage.

^{39.}
~~41.~~ (Original) A method for processing multiple textures as in claim ~~39~~³⁷ wherein input texture and rasterized color data comprise RGB and Alpha data.

^{40.}
~~42.~~ (Original) A multitexture processing subsystem as in claim ~~28~~²⁶ wherein an output of a current processing stage is made available as an input to a plurality of subsequent processing stages.

41.

43. (Currently amended) In a graphics system including a multitexture processing subsystem for selectively sampling texture data corresponding to one or more different textures and/or texture characteristics, said system comprising:

a recirculating texture unit including a texture coordinate processor, a texture mapper and a texture data feedback path that recirculates selected texture-mapped data from the texture mapper back to the texture coordinate processor; and

cut
a hardware shader for performing shading/blending operations that receives a first texture data sample and a subsequent texture data sample from said ~~multitexture processing subsystem~~ texture unit and recirculates an output from a shading/blending operation performed using the first texture data sample to an input of said shader for performing a shading/blending operation using the subsequent texture data sample and the output from the shading/blending operation performed on the first texture data sample, said shader shading/blending providing both color blend and alpha blend operations, wherein said texture coordinate processor interleaves the processing of direct and indirect texture coordinates.

42.

44. (Currently amended) A graphics pipeline including a multitexture processing subsystem that sequentially provides samples of multiple textures to a hardware shader that performs blending/shading operations on texture sample outputs of the multitexture processing subsystem, wherein the system includes a texture coordinate processor and wherein said hardware shader recirculates a resulting output of a blending/shading operation for performing a subsequent blending/shading operation of said resulting output

with a subsequent texture sample output, wherein said shader blending/shading operations provide both color blend and alpha blend operations, said texture coordinate processor interleaving the processing of direct and indirect texture coordinates.

43.

45. (Currently amended) A graphics processing pipeline that renders and displays images at least in part in response to polygon vertex data and texture data, comprising:

a recirculating texturing pipeline arrangement having a single texture address

coordinate/data processing unit, a single texture retrieval unit, and a texture lookup data feedback path for recirculating selected retrieved texture lookup data from the texture retrieval unit back to the texture address coordinate/data processing unit; and

a recirculating shade-tree alpha/color blender arrangement having a hardware shader connected to receive an output of the texture retrieval unit and a feedback path from an output of the hardware shader to an input of the shader for recirculating selected blended color or opacity output data, wherein the recirculating arrangement blends selected shader inputs to provide an output that is fed back for use as an input to the shader for a subsequent blending operation, wherein said alpha/color blender

arrangement provides both color blend and alpha blend operations, and

wherein the texture address coordinate/data processing unit interleaves the processing of direct and indirect texture coordinates.

44.

46. (Previously presented) A graphics processing pipeline that renders and displays images at least in part in response to polygon vertex data and texture data, comprising:

a recirculating texturing pipeline arrangement having a single texture address coordinate/data processing unit, a single texture retrieval unit, and a texture lookup data feedback path for recirculating selected retrieved texture lookup data from the texture retrieval unit back to the texture address coordinate/data processing unit; and

Y
Cmt a recirculating shade-tree alpha/color blender arrangement having a hardware shader connected to receive an output of the texture retrieval unit and a feedback path from an output of the hardware shader to an input of the shader for recirculating selected blended color or opacity output data, wherein the recirculating arrangement blends selected shader inputs to provide an output that is fed back for use as an input to the shader for a subsequent blending operation,

wherein said single texture address coordinate/data processing unit interleaves the processing of logical direct and indirect texture coordinate data.

45.
47. (Currently amended) In a graphics system, a multitexture processing subsystem comprising:

a texturing arrangement having a single texture address coordinate/data processing unit, a single texture retrieval unit, and a texture lookup data feedback path for recirculating retrieved indirect texture lookup data from a single texture retrieval unit back to the texture address coordinate/data processing unit; and

a recirculating hardware shader connected to receive an output of the texture retrieval unit, wherein the shader blends selected received outputs to provide a calculated color or opacity output that is selectively fed back for use as an input to the shader for a

subsequent blending operation, wherein said hardware shader provides both color blend and alpha blend operations, and wherein the texture address coordinate/data processing unit interleaves the processing of direct and indirect texture coordinates.

46.

48. (Previously presented) In a graphics system, a multitexture processing subsystem comprising:

a texturing arrangement having a single texture address coordinate/data processing unit, a single texture retrieval unit, and a texture lookup data feedback path for recirculating retrieved indirect texture lookup data from a single texture retrieval unit back to the texture address coordinate/data processing unit; and

a recirculating hardware shader connected to receive an output of the texture retrieval unit, wherein the shader blends selected received outputs to provide a calculated color or opacity output that is selectively fed back for use as an input to the shader for a subsequent blending operation, wherein said single texture address coordinate/data processing unit interleaves the processing of logical direct and indirect texture coordinate data.

47.

49. (Previously presented) A graphics processing pipeline that renders images based at least in part on polygon and texture data, comprising:

a recirculating texture unit including a texture coordinate processor, a texture mapper and a texture data feedback path that recirculates selected texture-mapped data from the texture mapper back to the texture coordinate processor; and

a recirculating shade-tree blender arrangement having shader inputs coupled to the recirculating texture unit, said recirculating shade tree blender blending selected shader inputs to provide outputs that are selectively fed back to said shader inputs for subsequent blender operations,

CS
Cml wherein said texture coordinate processor interleaves the processing of direct and indirect texture coordinates.